



CANUSA-CPS

A SHAWCOR COMPANY

Product Data Sheet

Canusa G Primer

Description:	Canusa G Primer is a specially formulated primer used to enhance the bond of mastic coated heat shrinkable sleeves on substrates that cannot be adequately cleaned or properly preheated..
Recommended use:	This primer is recommended for use on concrete, metal and fiberglass surfaces of manhole structures, waste water piping systems, and for the rehab coating for flowing liquid hydrocarbon pipelines.
Color:	Black, to brownish, opaque liquid with a solvent odor.
Typical Coverage:	200 to 300 square feet / gallon. Coverage varies with degree of porosity of substrate.
Typical Thickness:	3 to 4 mils
Number of Coats:	One
Shelf Life:	2 Years @ 72° F (23° C), Out of direct sunlight.
Flash Point:	96° F (20° C)
Thinner:	Do <i>not</i> dilute.
Minimum Curing Temperature:	10°C (50°F)
Safety:	Handle with care. Before and during use, observe all safety labels on packaging containers, consult CANUSA Material Safety Data Sheets and follow all local or national safety regulations. Harmful or fatal if swallowed; immediately seek medical assistance if swallowed. Avoid inhalation if possible solvent vapors or paint mist, as well as paint contact with skin and eyes. Apply only in well ventilated areas and ensure that adequate forced ventilation exists when applying paint in confined spaces or when the air is stagnant. Always take precautions against the risks of fire and explosions.

Applications



Manhole Structures



Waste Water Pipelines



Oil & Gas



Offshore Pipelines



Repair & Rehab



High Temp



Girth-Weld Joints

Configurations



Brush Application



Pad Application



3-Layer



Sleeve Compatible

Temperature Range



up to 80°C (176°F)

The product selection chart shown here is intended as a guide for standard products. Consult your Canusa representative for specific projects or unique applications. Below are typical values based on Heavy Duty (L-thickness) Sleeves.

Canusa G Primer



A SHAWCOR COMPANY

Canada

CANUSA-CPS
a division of SHAWCOR LTD.
25 Bethridge Road
Rexdale, Ontario
M9W 1M7,
Canada
Tel: +1 (416) 743-7111
Fax: +1 (416) 743-5927

U.S.A./Latin America

CANUSA-CPS
a division of SHAWCOR INC.
2408 Timberloch Place
Building C-8
The Woodlands, Texas
77380, U.S.A.
Tel: +1 (281) 367-8866
Fax: +1 (281) 367-4304

Europe/Middle East

CANUSA-CPS
a division of Canusa Systems Ltd.
Unit 3, Sterling Park
Gatwick Road
Crawley, West Sussex
England RH10 9QT
Tel: +44 (1293) 541254
Fax: +44 (1293) 541777

Asia/Pacific

CANUSA-CPS
BrederoShaw (S) Pte Ltd
101 Thomson Road
#17-01/02, United Square
Singapore
307591
Tel +65-6732-2355
Fax +65-6732-9073

www.canusacps.com

Canusa warrants that the product conforms to its chemical and physical description and is appropriate for the use stated on the installation guide when used in compliance with Canusa's written instructions. Since many installation factors are beyond our control, the user shall determine the suitability of the products for the intended use and assume all risks and liabilities in connection therewith. Canusa's liability is stated in the standard terms and conditions of sale. Canusa makes no other warranty either expressed or implied. All information contained in this installation guide is to be used as a guide and is subject to change without notice. This installation guide supersedes all previous installation guides on this product. E&OE

Printed on recycled paper. ♻ Recyclable. PDS-GPrimer-010